

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

### Revision date: 06.12.2016

Page 1 of 10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Mega Model Resin NF/ M+W Poly Resin UFI: HFM1-3RE5-H605-D9YN Product group: Liquid

1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Dental aid.

# 1.3. Details of the supplier of the safety data sheet

Company name:	megadental GmbH
Street:	Seeweg 20
Place:	D-63654 Büdingen
Telephone:	+49 (0) 6042-9755-0
e-mail:	info@megadental.de
Contact person:	Murat Büyük
e-mail:	info@megadental.de
	www.megadental.de

Telefax: +49 (0) 6042-9755-20

#### Vertrieben durch:

M+W Dental, Müller & Weygandt GmbH, Reichardsweide 40, 63654 Büdingen

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories: Flammable liquid: Flam. Liq. 2 Acute toxicity: Acute Tox. 4 Skin corrosion/irritation: Skin Irrit. 2 Serious eye damage/eye irritation: Eye Irrit. 2 Respiratory or skin sensitisation: Skin Sens. 1 Specific target organ toxicity - single exposure: STOT SE 3 Hazard Statements: Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

### Hazard components for labelling

Methyl methacrylate 2,2'-[(4-methylphenyl)imino]bisethanol Danger

Signal word:

**Pictograms:** 



#### Hazard statements

Highly flammable liquid and vapour.

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 2 of 10

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.

# **Precautionary statements**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Gently wash with plenty of soap and water.

#### 2.3. Other hazards

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixture based on mehtyl methacylat with chemical catalyst.

#### Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regula	ation (EC) No. 1272/2008 [CLP]			
80-62-6	Methyl methacrylate			60 - < 65 %	
	201-297-1		01-2119452498-28		
	Flam. Liq. 1, Skin Irrit. 2, Skin Ser	ns. 1, STOT SE 3; H224 H315 H31	7 H335		
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-diox	ne-1,16-diyl bismethacrylate	10 - < 15 %		
	Aquatic Chronic 3; H412				
3077-12-1	2,2'-[(4-methylphenyl)imino]biseth		1 - < 5 %		
	221-359-1				
	Acute Tox. 4, Eye Dam. 1; H302 I	H318			
2082-81-7	1,4-Butandiol dimethacrylate			1 - < 5 %	
	218-218-1				
	Skin Sens. 1; H317				

Full text of H and EUH statements: see section 16.

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### General information

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

## After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

### After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 3 of 10

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

#### 4.2. Most important symptoms and effects, both acute and delayed

Headache Drowsiness Causes skin and eye irritation. Skin sensitisation

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Water spray jet0 Carbon dioxide (CO2)0 Foam0 Extinguishing powder.

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

# 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

# Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

## 6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 4 of 10

### Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

#### 7.3. Specific end use(s)

Dental aid.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

### **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
80-62-6	Methyl methacrylate					
Worker DNEL,	long-term	inhalation		208 mg/m <sup>3</sup>		
Worker DNEL,	long-term	dermal		17 mg/kg bw/day		

#### 8.2. Exposure controls

### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

#### Eye/face protection

Suitable eye protection: goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### **Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

#### **Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless

according to Regulation (EC) No 1907/2006

## mega Model Resin NF

Revision date: 06.12.2016		Page 5 of 10
Odour:	characteristic	0
	characteristic	Test method
pH-Value:	not determined	rest metrioù
Changes in the physical state Melting point:	-48 °C	
Initial boiling point and boiling range:	100,3 °C	
Flash point:		DIN 51755
Flammability		
Solid:	not applicable	
Gas:	not applicable	
Lower explosion limits:	2,1 vol. %	
Upper explosion limits:	12,5 vol. %	
Ignition temperature:	435 °C	DIN 51794
Auto-ignition temperature		
Solid: Gas:	not applicable	
Decomposition temperature:	not applicable not determined	
Oxidizing properties	not determined	
Not oxidising.		
Vapour pressure:	37 hPa	
Density (at 20 °C):	0,94 g/cm³	
Water solubility: (at 20 °C)	15,3 g/L	
Solubility in other solvents not determined		
Partition coefficient:	log Pow 1,38	
Viscosity / dynamic: (at 20 °C)	0,53 mPa⋅s	
Vapour density:	not determined	
Evaporation rate:	not determined	
9.2. Other information		
Solid content:	not determined	
none		

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

oxidising0 Oxidising. Flammable0 Ignition hazard.

## 10.2. Chemical stability

May cause decomposition by long-term light influence.

# 10.3. Possibility of hazardous reactions

Exothermic reaction with: Combustible substance0 Alkali metals0 Alkaline earth metal0 Heavy metals0 Metal powder0 Acid0 Base. Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

mixtures with air.

### 10.5. Incompatible materials

Keep away from combustible material. Reducing agent Amines Heavy metals Peroxides Oxidising agent

#### 10.6. Hazardous decomposition products

Formation of: Oxygen.

### **SECTION 11:** Toxicological information

#### 11.1. Information on toxicological effects

#### Toxicocinetics, metabolism and distribution

The product has not been tested.

#### Acute toxicity

Harmful if inhaled.

## ATEmix tested

	Dose	Species	Source
LD50, oral	> 5000 mg/kg	Rat	
LD50, dermal	> 5000 mg/kg	Rabbit	
LC50, inhalative (vapour) (1 h)	29,8 mg/l	Rat	

CAS No	No Chemical name						
	Exposure route	Dose		Species	Source	Method	
80-62-6	Methyl methacrylate						
	oral	LD50 mg/kg	>5000	Rat	OECD 401		
	dermal	LD50 mg/kg	>5000	Rabbit			
	inhalative vapour	LC50	29,8 mg/l	Rat			
3077-12-1	2,2'-[(4-methylphenyl)i	2,2'-[(4-methylphenyl)imino]bisethanol					
	oral	LD50 mg/kg	> 300	Rat			
2082-81-7	1,4-Butandiol dimetha	crylate					
	oral	LD50 mg/kg	> 10000	Rat			
	dermal	LD50 mg/kg	> 3000	Rabbit			

### Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

#### Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate; 1,4-Butandiol dimethacrylate)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

Page 6 of 10

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 7 of 10

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Acute (short-term) fish toxicity

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
80-62-6	Methyl methacrylate						
	Acute fish toxicity	LC50	> 79 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	> 110	72 h	Selenastrum capricornutum	OECD 201	
	Acute crustacea toxicity	EC50	69 mg/l		Daphnia magna (Big water flea)	OECD 202	
	Crustacea toxicity	NOEC	37 mg/l		Daphnia magna (Big water flea)	OECD 202	
2082-81-7	1,4-Butandiol dimethacrylate						
	Acute fish toxicity	LC50	32,5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50	7,51 mg/l	48 h	Daphnia magna (Big water flea)	OECD 211	
	Crustacea toxicity	NOEC	7,51 mg/l		Selenastrum capricornutum		

### 12.2. Persistence and degradability

Biodegradable.

### 12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

# 12.4. Mobility in soil

Mobility in soil: No adsoption in soil or sediment.

#### 12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Other adverse effects

No information available.

# **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 8 of 10

## Waste disposal number of waste from residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

# Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
<u>14.3. Transport hazard class(es):</u>	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Transport category:	2
Hazard No:	339
Tunnel restriction code:	D/E
Other applicable information (land t	ransport)

#### Inland waterways transport (ADN)

<u>14.1. UN number:</u>	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
<u>14.3. Transport hazard class(es):</u>	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L

Other applicable information (inland waterways transport)

# Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
<u>14.3. Transport hazard class(es):</u>	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	-
Limited quantity:	1 L
EmS:	F-E, S-D

Other applicable information (marine transport)

## Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 1247
14.2. UN proper shipping name:	METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3

according to Regulation (EC) No 1907/2006

mega Model Resin NF			
Revision date: 06.12.2016		Page 9 of 10	
Limited quantity Passenger: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger: IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:	1 L 353 5 L 364 60 L		
Other applicable information (air trans E2 Passenger-LQ: Y341	sport)		
14.6. Special precautions for user Warning: Combustible liquid.			
<u>14.7. Transport in bulk according to Annex II of Marpol and the IBC Code</u> not applicable			
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture			
EU regulatory information			
2010/75/EU (VOC):	64,5 % (606,3 g/l)		
2004/42/EC (VOC):	64,5 % (606,3 g/l)		
Additional information To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC			
National regulatory information			
Employment restrictions:	Observe restrictions to employment for juvenils according to the 'ju protection guideline' (94/33/EC). Observe employment restrictions Maternity Protection Directive (92/85/EEC) for expectant or nursing	under the	
Water contaminating class (D): Skin resorption/Sensitization:	3 - highly water contaminating Causes allergic hypersensitivity reactions.		
15.2. Chemical safety assessment			
Chemical safety assessments for substances in this mixture were not carried out.			
SECTION 16: Other information			

# Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

# Relevant H and EUH statements (number and full text)

Extremely flammable liquid and vapour. Highly flammable liquid and vapour. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

according to Regulation (EC) No 1907/2006

# mega Model Resin NF

Revision date: 06.12.2016

Page 10 of 10

Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Harmful to aquatic life with long lasting effects.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)